

IVECO DAILY - 3500PLUS SPECIFIKACE

BE-Combi je nezávislý na značce a dosahuje maximálního užitečného zatížení pro nejoblíbenější značky užitkových vozidel. Níže naleznete přehled specifikací pro Iveco Daily, který je také k dispozici ke stažení v dolní části stránky.



IVECO DAILY 40C & 50C

The model must be factory fitted with these options	Code
Digital smart tachograph	00821
13-pin connection	06520
Heavy-duty alternator 220 Amp	72837
Bodybuilder connector for surface-mounting	08656
Reinforced 7-leaf suspension	02240
No spare tire	02213
No spare tire carrier	00724
Without rear bumper	00169
Reversing camera supplied separately	00344
Without parking sensors	06327
Exterior mirrors on extended arm (width 2,350 mm)	73024
Speed limiter 100 km/h	06358
Note: Order a 4.44 rear axle reduction	00003
Reinforced Quad-Tor front axle 2,100 kg	n/a
Adaptive cruise control can be ordered	
180 hp engine preferred (160 hp possible)	
Order the Iveco Daily as N1 (3,500 kg gross weight)	
If equipped with a cooling unit, order the appropriate option(s) as well	

Possibilities BE-Combi 3500PLUS System

Wheelbase	Maximum body length	Minimum body length with tail lift	Minimum body length without tail lift
3.750 mm	4.700 mm	4.700 mm	4.500 mm
4.100 mm	5.200 mm	5.200 mm	5.000 mm
4.350 mm	5.700 mm	5.200 mm	5.200 mm

Information for body builder

- Maximum tail lift weight: 1,000 kg.
- The trailer is supplied without legally required lighting and bumper.
- Connections such as the cooling unit, hydraulics, or other connections must **ALWAYS BE DISCONNECTABLE**.

Standard BE-Combi 3500PLUS System

- Trailer mudguard set (please note when requesting a body builder)
- Supports for mounting the tail lift

Option BE-Combi 3500PLUS System

Landing legs for uncoupling the trailer

BE-Combi International B.V.

Azewijnseweg 12

4214 KC Vuren

+31 (0) 345 - 633 644

verkoop@be-combi.nl

www.be-combi.nl