


MAN TGE - 3500PLUS SPECIFICATIONS

BE?Combi is brand?independent and delivers maximum payload capacity for the most well?known commercial vehicle brands. Below you will find an overview of the specifications for the MAN TGE, which is also available for download at the bottom of the page.



MAN TGE

MAN TGE 5.0 T must be equipped with the following options	Code
Multifunctional control unit	IS2
Front axle 2.100 kg.	VV8
Suspension / Damping reinforced	2MR / 2MT
AGM batterie with bigger capacity	NY4
Rearview mirrors with extended bracket > 2.160 mm.	3BL / 3AQ
Digital Tachograph	9NI
Preparation towing hook	1D7
If 1D7 not available, order complete towing hook	1D1
Snelheidsbegrenzer op 100 km/h	7H2
Position lights on cabin roof	6S3
Registration as 3,5 ton	07H
Incomplete N1 homologation	5ET
Rear lights with longer cables	8SE
Speed limiter 100 km/u	7H2
Voertuig aanleveren met uitgeschakelde transport modus	2A7
Without parking sensors	7X0
Preparation rear view camera	KA8
Without blind spot radar	BR0
Transportmodus deactivated	2A7
Extra battery always in combination with option IS2	
Automatic gearbox recommended	n/a
Engine minimum 120 kW	n/a

Options BE-combi 3500PLUS systeem

Wheelbase	Maximum body length	Minimum body length plus tail lift	Minimum body length no tail lift
3.640 mm	4.700 mm	4.700 mm	4.500 mm
4.490 mm	5.200 mm	5.200 mm	5.200 mm

Information for the body builder

- Tail lift capacity max. 1.000 kg.
- The trailer is delivered without legally required lighting and rear bumper
- Connections such as cooling machine, hydraulics or other connections must **always be disconnectable**.

BE-Combi Sales & Rental B.V.

Azewijnseweg 12

4214 KC Vuren

+31 (0) 345 - 633 644

verkoop@be-combi.nl

www.be-combi.nl